




SafePace® 475 Driver Feedback Sign

The Traffic Logix® SafePace® 475 driver feedback sign is an 18" digit, full size radar sign. It can be mounted at multiple locations with a universal mounting bracket and can function autonomously for weeks at a time with optional battery power.



Choice of faceplate colors available

475 Specifications

| | |
|-----------------------|---------|
| Digit Size | 18" |
| Height | 42" |
| Weight | 53 lbs |
| 24/7, 365 Scheduling | ✓ |
| Data Collection | ✓ |
| Solar Compatibility | ✓ |
| Battery Operated | ✓ |
| Universal Mounting | ✓ |
| Cloud Compatibility | ✓ |
| Trailer Compatibility | ✓ |
| Dolly Compatibility | ✓ |
| Hitch Compatibility | ✓ |
| Warranty | 2 Years |

Features

MUTCD compliant with static "YOUR SPEED" message and highly visible 18" LED digits that are visible from up to 1000 feet away.


User friendly software interface allows you to manage sign parameters such as threshold speeds and violator strobe remotely

Ultra low power consumption including the most power-efficient radar technology available, optional solar power, and optional battery power that allows the sign to function autonomously for **up to five weeks**

Superior construction and durability for long-lasting performance

High strength aluminum sign face and individual optical lenses to **protect against vandalism and theft**

Stealth Mode allows the sign to collect baseline traffic data while speed display appears blank to motorists



| Feature | Specifications |
|-------------------------------------|---|
| Dimensions | |
| Digits | 18"(h) x 9.6"(w), 112 LEDs per digit |
| Text | Letters 6.0" (h) spell "YOUR SPEED" fixed message, 2 lines |
| Unit alone | 24.6"(h) x 29.5"(w) x 3.5"(d) |
| Unit with "YOUR SPEED" sign mounted | 42.0"(h) x 31.5"(w) x 3.5"(d) |
| Sign Weight | |
| AC Powered | 42 lbs |
| 4 cell battery powered model | 53 lbs (3 batteries) |
| Solar powered model | 42 lbs (not including solar panel or bracket) |
| General Specifications | |
| Operating Temperatures F (C): | -40° (-40°) to 185° (85°) |
| Speed Units | Miles per hour (mph) or Kilometers per hour(km/h) |
| Faceplate | Yellow or white high-Intensity prismatic reflective sheeting on sign face with black colored text MUTCD approved colors and format |

| Feature | Specifications |
|--|---|
| Bashplate | Aluminum, 0.1875" |
| Communications | Bluetooth (standard) GSM/GPRS (optional, for use with SafePace Cloud) |
| Programming | SafePace Pro sign management software SafePace Cloud remote sign management 24/7 365 day unlimited programming and scheduling |
| Power Options (Electrical Specifications) | |
| AC power input | 100~240 V AC |
| DC power input | 12 V DC |
| Solar panel options | 50W, 90W |
| Radar | |
| Internal | Doppler (FCC approved) |
| Radar RF out | 5 mW maximum |
| Radar f-center | 24.125 GHz +/- 25 MHz |
| Pickup distance | Up to 1,200 feet |
| Beam | 11° x 11°, Linear polarization |
| Display | |
| LEDs | 245 |
| Digits | 224 Amber, 23°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) |
| Speed Violator Strobe | 21 White, 15°, 5 mm , luminous intensity (18,000 – 28,000 mcd/LED) |
| Optical Lenses | 245 |
| Ambient light sensors | 2 sensors and automatic brightness control |
| Enclosure | |
| Construction | 12 gauge aluminum, flat black powder coated front for reduced glare and maximum contrast; light gray powder coated body to minimize heat absorption |
| Weatherproof Rating | Weatherproof, NEMA 4X-12, IP65 level compliant Non-sealed and ventilated |
| Warranty | |
| Sign | 2 years |
| Batteries | 1 year |