


SafePace® Evolution 11

The Traffic Logix SafePace® Evolution 11 driver feedback sign is the solution that fits your budget.

This compact radar speed sign offers exceptional visibility and power efficiency in a lightweight and portable solution. Featuring the options you need at remarkably affordable pricing, the SafePace Evolution 11 driver feedback sign will help you keep your neighborhoods safe for years to come.









| EV 11 Specifications | |
|-----------------------|----------|
| Digit Size | 11" |
| Height | 29" |
| Weight | 20 lbs |
| 24/7, 365 Scheduling | ✓ |
| Data Collection | ✓ |
| Solar Compatibility | ✓ |
| Battery Operated | ✓ |
| Universal Mounting | ✓ |
| Cloud Compatibility | ✓ |
| Trailer Compatibility | ✓ |
| Dolly Compatibility | ✓ |
| Hitch Compatibility | ✓ |
| Warranty | 2 Years |

Features

Energy Efficient: The sign can function up to 3 weeks autonomously with optional battery power depending on volume.


User-Friendly: Easy-to-use management software lets you set sign parameters quickly and easily while optional data collection allows you to download traffic data, and generate statistical reports.

Stealth Mode: Baseline traffic data collected while speed display appears blank to motorists.

Speed Violator Strobe: Programmable flashing strobe to alert speeding drivers comes standard with every sign.

Universal Mounting: Optional mounting brackets let you use one sign at multiple locations with the turn of a key.

Superior construction and durability for long-lasting performance.



| Feature | Specifications | |
|--|--|--|
| Dimensions | | |
| Digits | 11"(h) x 5.6"(w), 98 LEDs per digit | |
| Unit with "YOUR SPEED" sign mounted | Full size sign: 29.0"(h) x 23.0"(w) x 5.625"(d) | |
| Sign Weight (includes "YOUR SPEED" sign (2 lbs) mounted) | | |
| AC Powered | 20 lbs | |
| Battery Powered Model | 20 lbs (not including batteries) | |
| Solar powered model | 20 lbs (does not include batteries, solar panel or bracket) | |
| General Specifications | | |
| Operating Temperatures F (C): | -40° (-40°) to 185° (85°) | |
| 2-Digit Speed Display | Miles per hour (mph) 3-99. Kilometers per hour (km/h) 5-99. | |
| Faceplate | High-Intensity prismatic reflective sheeting on "YOUR SPEED" signs with black colored text. MUTCD approved colors and format | |
| Communications | Bluetooth, GSM/GPRS | |
| Programming | SafePace® Pro management software SafePace® Cloud remote management 24/7 365 day unlimited programming and scheduling | |

| Feature | Specifications | | |
|---|---|--|--|
| Power Options (Electrical Specifications) | | | |
| AC power input | 100~240 V AC | | |
| DC power input | 12 V DC | | |
| Solar panel options | 20W or 50W solar panel | | |
| Radar | | | |
| Internal Radar: | Doppler (FCC approved) | | |
| Model | DF 600 | | |
| Radar RF out | 5 mW maximum | | |
| Radar f-center | 24.125 GHz or 24.200 GHz | | |
| Pickup distance | Up to 400 feet | | |
| Beam angle | 24° (vertical) x 12° (horizontal) | | |
| Beam polarization | Linear | | |
| CE Mark (Radar) | Yes | | |
| | Display | | |
| LEDs | 208 | | |
| Digits | 196 LEDs: Color: Yellow (590 nm) Viewing angle at 50% IV: 30° Partial Flux (Brightness): 9000 – 22400 Ev,[lux]/LED | | |
| Speed Violator Strobes | Color: White (2700 K – 6500 K) Viewing angle at 50% IV: 150° Luminous Flux: typically 33lm @ 4000 K Luminous Efficacy: typically 176 lm/W @4000 K | | |
| Ambient light sensor | 1 sensor and automatic brightness adjustment | | |
| Enclosure | | | |
| Construction | Vandal resistant, lightweight polymer. Matte black front for reduced glare and maximum contrast. Light gray body to minimize heat absorption | | |
| Weatherproof Rating | Weatherproof, NEMA 4X-12, IP65 level compliant. Non-sealed and ventilated | | |
| | | | |
| | Warranty | | |
| Sign | Warranty 2 years | | |